

United States Patent Application

For

A METHOD AND SYSTEM FOR UNIVERSAL PACKAGING IN CONJUNCTION  
WITH A BACK-END INTEGRATED CIRCUIT MANUFACTURING PROCESS

Inventors:

BO SOON CHANG  
VANI VERMA

Prepared by:

WAGNER, MURABITO & HAO LLP  
Two North Market Street  
Third Floor  
San Jose, California 95113

# A METHOD AND SYSTEM FOR UNIVERSAL PACKAGING IN CONJUNCTION WITH A BACK-END INTEGRATED CIRCUIT MANUFACTURING PROCESS

## RELATED UNITED STATES APPLICATION

5           This application claims priority to the provisional United States Patent Application, Serial Number 60/272,283, Docket CYPR-PM01008.PRO, entitled "Automated and/or Integrated Process and/or Equipment for Assembling, Packaging, Finishing, and/or Testing," filed February 27, 2001, and assigned to the assignee of the present application which is hereby incorporated by reference.

## FIELD OF THE INVENTION

10           The present invention relates to the field of integrated circuit (IC) chip manufacturing. More particularly, embodiments of the present invention relate to a method of back-end manufacturing IC packaged chips using an integrated  
15           automated back-end IC manufacturing assembly.

## BACKGROUND ART

20           Conventional back-end IC manufacturing facilities, at contract assembly houses as well as several original equipment manufacturers (OEMs), have a moderate to low level of automation and equipment integration. These lines typically require several manual steps and depend upon operator intervention for many, if not nearly all, operation, maintenance, lot management and inspection steps. Since this is typically a batch type process, there maybe a high level of work-

in-progress (WIP) inventory, as well as relatively high cycle times. This type of factory management may not be suitable for manufacturing where flexibility is key, and daily operation may require several changeovers in die, package and leadframe types.

5

Presently, the back-end manufacturing process for ICs (i.e. from manufactured wafer to tested and packaged die) is labor intense. In order to manufacture an IC chip, in the back-end, from the initial step of wafer reception to the packaging and shipping of the finished chip, there are many personnel and specialized pieces of equipment involved. Further, the process of back-end manufacturing an IC chip is a relatively long one. The complete process typically takes anywhere from four to six weeks to obtain a final packaged chip, and generally takes on the order of 1.5 to 2 weeks when using special "rush" or "hot lot" procedures.

10

15

Due to the length of the back-end manufacturing process and the required manpower, IC chips are generally manufactured in batches. That is, the process of back-end manufacturing a single IC is done on a large scale with individual large batches running through discrete process steps. This large scale is utilized to add a standard of efficiency to an otherwise complex process. For instance, a wafer that is received from an outside vendor is cut into strips. Each strip may contain approximately 200 die, and there may be 50 strips in a batch. Therefore, a typical

20

batch of ICs, formed through a single back-end IC manufacturing process, may contain 10,000 or more IC chips.

An embodiment of a conventional batch-oriented back-end IC manufacturing process is illustrated in Figure 1. This embodiment illustrates the length of a conventional back-end IC manufacturing process. Batches of chips move from one stage of the process to the next. In block diagram 100, the back-end manufacturing line includes front-of-line portion 100A, end-of-line portion 100B, test 128, and finish portion 100C. The back-end IC manufacturing process begins with die attach station (D/A) 110. Although a die preparation process is required, this is typically done outside front-of-line portion 100A. Furthermore, the die preparation process may take place in a different location than the rest of the back-end IC manufacturing process.

Front-of-line portion 100A includes die attach station (D/A) 110, cure station 112, plasma treatment station 114, wire bond station (W/B) 116, and another plasma station 118 (typically a plasma cleaning station). This back-end IC manufacturing process includes many aspects which require human material handling stations (HM) 150. HM 150 steps are represented in Figure 1 with arrows. These HM 150 steps include transferring the batch from one step of the process to the next, as well as between specific manual visual inspection stations (MVI) 105.

In the front-of-line portion 100A, the cure station 112 may carry out a curing process in a machine designed to heat a batch of strips to a temperature of about 150 degrees Celsius, for a period of one hour, in order to cure the glue used in the die attach step. This cure station 112 is followed by a plasma station 114 cleaning step utilizing oxygen (O<sub>2</sub>) or Argon (Ar). The next step is wire bond station (W/B) 116 followed by MVI 105. Another plasma station 118 cleaning step is done following wire bond station (W/B) 116 and another MVI 105. The plasma station 118 cleaning step is similar to plasma station 114 cleaning step, and each plasma step may last anywhere from 30 minutes to one hour.

With reference still to Figure 1, back-end manufacturing line 100 continues with an end-of-line portion 100B where need for human interaction also exists. End-of-line portion 100B begins with mold station 120. HM 150 is utilized to move the batch through each MVI 105. The next step in end-of-line portion 100B is post mold cure station (PMC) 122. PMC 122 is a curing step which requires a temperature of 175-degree Celsius and a timeframe of approximately 5 hours. After PMC 122, the strip undergoes solder ball attach station (SBA) 124. Following SBA 124, MVI 105 takes place to ensure proper attachment of the ball to each strip in the batch. The batch is then processed through saw station 126. Saw station 126 separates the batch into individual IC chips. The final step in end-of-line portion 100B is MVI 105 of the completed saw station 126 step. Throughout the back-end manufacturing

process, MVI 105 normally includes additional quality control and assurance measures.

Following the completion of end-of-line portion 100B, back-end IC  
5 manufacturing line 100 continues with test portion 128. In test portion 128, as illustrated in the previous portions, the need for human interaction includes human handling during both the testing, and inspecting phases.

20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 267

to control production overruns, a manufacturer will normally use a build-to-forecast model based on contract back-end IC manufacturing techniques.

Disadvantages of the batch level process include the large minimum order size and the long timeframe for the manufacture of a specific type of IC. For example, if a customer requests an uncommon or highly demanded type of IC, e.g., one that is not in inventory, they would typically place a special order. In this case, a small order may not be economically worthwhile. Specifically, the batch level process is generally cost prohibitive unless the customer orders a specified minimum amount of product. Further, it generally takes a minimum of four to six weeks to process a special order. Moreover, this minimum time conventionally includes time to reset and/or maintain machinery, and/or instruct inspectors on expected differences in the back-end IC manufacturing process.

Another disadvantage of the conventional batch process is the multitude of procedures using human interaction with the batch in transporting the batch from stage to stage, or during certain stages, such as visual inspection (HM). These procedures include MVI, quality assurance (QA), and handling throughout the entire back-end IC manufacturing process. Specifically, MVI typically involves a pause in the back-end IC manufacturing process so that an operator can manually inspect the IC chip after a given step. MVI is done to ensure correct part placement, proper IC shape, elimination of excess material on the IC, etc. MVI, however, is

error prone because it relies on human judgment and discrimination, and it may be tedious, and may require sustained or prolonged concentration, thereby introducing difficult practice for periods of time in excess of an hour or two, or over an entire workday.

5

Further, upon completion of the visual inspection, a QA examination takes place to ensure the MVI was done correctly. This QA examination further delays the back-end IC manufacturing process due to an increase in overall time spent on the redundant inspection. Another detrimental aspect of the MVI process is the human handling of the strips in the batch. As an inspector analyzes a die on a strip in the batch, they may inadvertently cause a defect. Thus, an inspector looking for defects may actually be creating them.

A further problem arises in batch back-end IC manufacturing in that a relatively large number of personnel are required, e.g., personnel to move the batch from point to point, personnel for MVIs, personnel for QA inspections, and personnel to operate each of the many processes required in typical IC back-end IC manufacturing. The average processing line may easily maintain a payroll of thirty-plus personnel. Therefore, the expense required per employee must be factored into the final cost of the IC chip.



Early efforts in equipment integration and automation result in “islands of automation” involving some automation at an individual equipment level, but not a high level of multi-equipment integration. Individual operation steps at the level of an individual piece of equipment had been automated to some degree, but still manual inspection, as well as manual lot movement and tracking remained typical. Further improvements in equipment and software capabilities have transitioned these islands to automation cells that handle large chunks of the assembly process. Each cell is a functional area and represents part of the total operation. However, a total solution has not been presented heretofore.

5

2022-09-01 10:56:00

## SUMMARY OF INVENTION

Thus, a need exists for a method and system for universal packaging in conjunction with a back-end IC manufacturing process. A further need exists for a method and system for universal packaging in conjunction with a back-end IC manufacturing process, which can proficiently perform IC packaging on a smaller scale of chips. A further need exists for a method and system for universal packaging in conjunction with a back-end IC manufacturing process which can abbreviate the MVI and QA process while maintaining a higher quality of visual inspection. Still another need exists for a method and system for universal packaging in conjunction with a back-end IC manufacturing process which requires fewer personnel to maintain a packaging line. A further need exists for a method and system for universal packaging in conjunction with a back-end IC manufacturing process which is compatible with existing back-end IC manufacturing processes.

One embodiment of the present invention advances factory automation by implementing an advanced, fully integrated assembly and test lines capable of manufacturing ball grid array (BGA) packages (for example, molded BGA packages in a matrix array). The implementation has integrated the manufacturing process from die attach to tape and reel, with a reduced cycle time. This implementation enables a virtually "hands-free" production line with automated chip movement, testing, inspection and sorting as well as automated chip assembly.

2022-05-04 10:00:00

The present invention provides, in various embodiments, methods to integrate a IC chip manufacturing assembly. Embodiments of the present invention also provide an integrated in-line back-end IC manufacturing assembly process, which proficiently performs IC packaging manufacturing on a smaller scale. The present invention further provides a method and system for universal packaging in conjunction with a back-end IC manufacturing process, which reduces the human-operated MVI and QA processes while maintaining a higher quality of visual inspection. The present invention also provides a method and system for universal packaging in conjunction with a back-end IC manufacturing process which requires fewer personnel on the manufacturing line. The present invention further provides a method and system for universal packaging in conjunction with a back-end IC manufacturing process, which is compatible with existing back-end IC manufacturing processes.

Generally, an embodiment is directed to an integrated assembly process that automatically moves small amounts of IC chips (e.g. a die strip) through packaging stages that span from receiving the IC dies to testing the packaged chip and tape and reel assembly. Herein, the processing of IC chips in a pipeline fashion is called "in-line" assembly because the individual chips (in small amounts) are moved from station to station very rapidly and are not delayed in batch fashion. In-line assembly is different from batch processing, in that, small amounts of chips move through the entire assembly process of the present invention (in a pipeline fashion) from

one end to another without interruption or delay associated with batch processing. Handling, testing and processing the chips are also automated processes in accordance with the present invention to reduce and/or eliminate human interactions.

5

Specifically, in one embodiment, the present invention processes a die-strip through a number of integrated in-line processes that function independently of the die size of the die-strip. A control computer maintains a die-strip map database recording the die size of the die-strip. In-line molding and solder ball attachment processes are then performed and function independently of the die size of the die-strip. Processes that are independent of die size provide a universal packaging manufacturing solution. The present invention then accesses the database to determine the die size for cutting the die-strip based on specifications maintained by the electronic die-strip map database. Sorting, testing and finish assembly processes are then performed.

In one embodiment, the various substations of the integrated in-line back-end IC manufacturing hardware are arranged in an assembly line format. Further, a software process monitors and controls the integrated in-line back-end IC manufacturing hardware. It is also appreciated that an automated reject management protocol is implemented from initial die attach through test and finish. Specifically, the reject management protocol maintains a strip process

history which is updated via an electronic strip map database 620 throughout the manufacturing process using comprehensive strip level tracking procedure. The updates to the electronic strip map database 620 are received through a network hierarchy including automated visual camera technology, integrated cell controllers, and an overall manufacturing execution system. These elements virtually eliminate human manual intervention in the inspecting, testing and sorting of IC chips.

In one embodiment, a universal packaging process is applied to the in-line assembly line manufacturing process. Specifically, universal packaging utilizes the in-line subassemblies in conjunction with the integrated software processes to increase throughput time of a specific package size. A further benefit is realized with the streamlined transition of subassembly manufacturing specifications from one package size to another. In general, aspects of universal packaging allow package changeovers with minimal changeover times, thus allowing some amount of flexibility within package families. For example, in one embodiment, an exemplary changeover in the entire line from a 7mm x 7mm package to any other package size may take less than thirty minutes.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention:

5

CONVENTIONAL ART FIGURE 1 is a block diagram illustrating a conventional batch processed back-end IC manufacturing line.

FIGURE 2 is a block diagram illustrating an exemplary integrated in-line back-end IC manufacturing assembly line and assembly method in accordance with one embodiment of the present invention.

FIGURE 3A is a block diagram illustrating an exemplary front-of-line portion of the novel integrated in-line back-end IC manufacturing line and method in accordance with one embodiment of the present invention.

FIGURE 3B is a block diagram illustrating an exemplary end-of-line portion of the novel integrated in-line back-end IC manufacturing line and method in accordance with one embodiment of the present invention.

20

FIGURE 3C is a block diagram illustrating an exemplary finish portion of the novel integrated in-line back-end IC manufacturing line and method in accordance with one embodiment of the present invention.

5        FIGURE 4 is a block diagram illustrating an exemplary electronic die-strip map database in accordance with one embodiment of the present invention.

10        FIGURE 5 is a block diagram of an exemplary process of an electronic inspection and die-strip map database updating method in accordance with one embodiment of the present invention.

FIGURE 6 is a block diagram of exemplary reject management system in accordance with one embodiment of the present invention.

15        FIGURE 7 is a block diagram illustrating an exemplary reject management and sorting system in accordance with another embodiment of the present invention.

20        FIGURE 8 is a flow chart of steps in an exemplary method for processing a chip through integrated in-line back-end IC manufacturing hardware in accordance with one embodiment of the present invention.

FIGURE 9 is a flow chart of steps for software integration in accordance with one embodiment of the present invention.

FIGURE 10 is a flow chart of steps for reject management protocol used in conjunction with the in-line integrated in-line back-end IC manufacturing assembly in accordance with one embodiment of the present invention.

FIGURE 11 is a flow chart of steps in an exemplary method for universal packaging in accordance with one embodiment of the present invention.

FIGURE 12 is a block diagram of an exemplary general purpose computing system in accordance with one embodiment of the present invention.

FIGURE 13 is a block diagram of an exemplary method of electronic inspection and strip map database updating in accordance with another embodiment of the present invention.

The drawings referred to in this description should be understood as not being drawn to scale except if specifically noted.



## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with the preferred embodiments, it will be understood that they are not intended to limit the invention to these embodiments. On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be obvious to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

Moreover, some portions of the detailed descriptions which follow are presented in terms of procedures, logic blocks, processing and other symbolic representations of operations for fabricating IC structures. These descriptions and representations are the means used by those skilled in the art of IC fabrication to most effectively convey the substance of their work to others skilled in the art. In the present application, a procedure, logic block, process, or the like, is conceived to be a self-consistent sequence of steps or instructions leading to a desired result.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing terms such as "establishing," "coupling," "monitoring," and "utilizing," or the like, refer to actions and processes (e.g. Figures 2-13) of back-end IC manufacturing.

## OVERVIEW

Back-end IC manufacturing, in one example, refers to IC packaging and other assembly functions performed typically at or past "front-of-line" assembly time. This may include, "front-of-line" assembly, "end-of-line" assembly, "test", and/or "finish" assembly.

Embodiments of the present invention concern an integrated, software-driven, in-line module for assembling, testing and /or finishing ICs that, in one embodiment, contains multiple substations, e.g., machines, from die attach through tape and reel (in one embodiment having a length of about 120 feet), connected with cell controllers to a higher level manufacturing execution system (MES) and factory planning information. In effect, the system works like a single assembly-test-finish equipment integrating all the individual processes into one assembly step using software and hardware integration. All this integrated equipment allows a rapid

package changeover with similar package size families, allowing flexibility in production capabilities.

The present embodiment advantageously uses automated strip conveyor systems and robotic arms. In one embodiment, there is no human handling of substrate strips or IC units at all, and all human inspection, either offline or online, may be replaced with machine auto-vision. In addition to better inspection quality, machine auto vision also allows quality assurance (QA) simultaneously with production. The present embodiment simplifies the overall assembly process by eliminating offline processes and/or reducing in-line batch processes like curing, plating, and dry baking (e.g. converting such batch processes to continuous processes).

In one embodiment, the exemplary platform package may be a matrix array “die-strip” (e.g. an n-by-m matrix array of die on a single substrate, where n and m are each independently an integer of  $\geq 2$  preferably from 3 to 15, more preferably from 4 to 10) molded ball grid array (BGA) package. Array-based package-independent processing lends itself to the goals of automation and integration.

## INTEGRATED HARDWARE

In the following discussion, Figures 2-8 illustrate the hardware integration process of the present embodiment broken into four assembly portions. Including front-of-line, end-of line, test, and finish.

5

Figure 2 is a block diagram illustrating an integrated in-line back-end IC manufacturing assembly (process) 200 in accordance with one embodiment of the present invention. Figure 2 begins with the die attach (D/A) substation 304 that performs the D/A process and ends with tape and reel assembly 328. Any die preparation processes may be used with the present embodiment.

10

Figures 3A-3C are block diagrams illustrating more detailed versions of line 200 of Figure 2. Specifically, Figure 3A is front-of-line assembly portion 300A, Figure 3B is end-of-line assembly portion 300B, and Figure 3C is finish assembly portion 300C.

15

Figure 8 is a flow diagram for illustrating pertinent process steps associated with line 200. With reference now to step 802 of Figure 8 and to Figure 3A, the present embodiment processes die-strip 400 through front-of-line assembly portion 300A. As described above, the implementation of a single die-strip 400 traveling through line 200, allows for a more personal approach to the manufacturing process. Specifically, since only a single die-strip 400 is processed through each substation, an

20

order may be placed for a number of IC chips which is smaller than the conventional art batch size without ensuing the extraordinary costs previously associated with a small run. It is also relevant that the difference in size between a single die-strip 400 and a batch containing 50 or so die-strips, enables smaller more efficient machinery to be utilized during line 200. In general, the present embodiment processes die-strip 400 individually in an in-line fashion. Therefore, the batch process used by the conventional art is removed from the integrated in-line back-end IC manufacturing method of the present embodiment.

Now, with reference to step 802 of Figure 8 and Figure 3A, the front-of-line assembly portion 300A comprises a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations include die attach substation (D/A) 304, cure substation 306, plasma substation 308, wire bond substation (W/B) 310, and plasma substation 312. In the present embodiment, many portions of the conventional line process have been modified in order to establish an in-line assembly line format.

Front-of-line portion 300A receives a die-strip (an example of a die-strip 400 is illustrated in Figure 4) at the die attach substation 304 that performs the die attach (D/A) process. However, the actual cutting and shaping of the wafer, from which die-strip 400 is formed, may take place outside of the scope of the present embodiment.

Substation 304 performs the initial processes of attaching die to a strip thereby forming a die-strip 400. Specifically, D/A substation 304 attaches a die (for example, a BGA die) to die strip 400 (Fig. 4). In the present embodiment glue is used to attach die to die strip 400. The glue may be any glue utilized by one skilled in the art. It is appreciated that any well-known die preparation process may be used with the present embodiment.

The second step in front-of-line assembly portion 300A is performed by cure substation 306 that performs the cure process. In general, cure substation 306 performs an in-line process for drying the adhesive between die and substrate used in D/A substation 304. That is, die strip 400 remains at cure substation 306 until the glue is cured and die is fixedly coupled to die strip 400. The third step is plasma substation 308 that performs a plasma process. Specifically, plasma substation 308 performs an in-line cleaning substation that is applied to both sides of die strip 400 in order to clean any excess glue from die and die strip 400. In general, in-line plasma substation 308 may utilize any number of well-known cleaning processes.

The forth step in front-of-line assembly portion 300A is performed at W/B substation 310. W/B substation 310 performs an in-line process for wire bonding die strip 400. The final step in front-of-line assembly 300A is performed by plasma substation 312. Plasma substation 312 performs an in-line cleaning process applied

to both sides of die strip 400 in order to clean any excess wire bonding material from die strip 400.

With further reference to step 802 of Figure 8 and Figure 3A, the present  
5 embodiment reduces most processing times established by the sub-stages of the  
conventional art. For instance, in the present embodiment, cure process and  
substation 306 is a snap cure which takes approximately 2 minutes. In addition, both  
plasma cleaning processes and substations (e.g. plasma substation 308 and plasma  
substation 312) have been reduced in length to approximately one minute. The  
10 reductions in processing time are a result of both the reduced processing size and in-  
line nature of the present embodiment. That is, since the present embodiment is  
applied at a die-strip 400 level and since each die-strip 400 is maintained in a  
controlled environment, many time consuming steps of the conventional art batch  
process have been reduced. Specifically, the internal areas of the in-line processing  
15 stations are reduced significantly. This reduction results in less time required for  
heating, venting, vacuuming, etc. Further, with no need for human interaction, the  
processing environment may be maintained at peak proficiency.

With further reference to step 802 of Figure 8 and Figure 3A, in the present  
20 embodiment human handling situations have been removed. This removal of  
human interaction is obtained by the implementation of specific manufacturing  
aspects. The first aspect is the integration of the hardware. Specifically, the

integration of an in-line assembly process results in automated movement of die-strip 400 from one process to the next. The second aspect is the introduction of vision camera systems (V/C) 302 at D/A substation 304 and W/B substation 310. Specifically, V/C 302 assumes all aspects of the inspection and QA requirements previously performed by hand. Further details of V/C 302 are covered in the software process outlined herein.

With reference now to step 804 of Figure 8 and Figure 2, the present embodiment automatically, in an in-line fashion, provides die-strip 400 from the front-of-line assembly portion 300A to an end-of-line assembly portion 300B. Analogous to the front-of-line assembly portion 300A, the end-of-line assembly portion 300B contains many in-line substations. Also, as illustrated in the previous front-of-line assembly portion 300A, need for human interaction within the manufacturing process is eliminated.

With reference now to step 806 of Figure 8 and Figure 3B, the present embodiment processes die-strip 400 through the end-of-line assembly portion 300B having a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations in end-of-line assembly portion 300B include mold substation 314, post mold cure (PMC) substation 316, solder ball attach (SBA) substation 318, saw substation 320, and sort substation 322.



The first process in end-of-line assembly portion 300B is performed at the mold substation 314. In general, mold substation 314 utilizes a molding compound injection. Specifically, mold substation 314 is an in-line process that places a protective layer of material above die strip 400. In the present embodiment mold substation 314 may be a plastic or any other type of non-conductive material which can act as a layer of protection.

The second step in end-of-line assembly portion 300B is performed by the PMC substation 316. In general, PMC substation 316 performs an in-line process for drying the non-conductive material used at mold substation 314. That is, die strip 400 remains at PMC substation 316 until the molding material is cured, thereby ensuring that die is protectively covered on die strip 400.

The third step in end-of-line assembly portion 300B is performed at the SBA substation 318. Specifically, SBA substation 318 performs an in-line process for attaching a solder ball to die strip 400. The forth step in end-of-line assembly portion 300B is performed at the saw substation 320. Saw substation 320 performs an in-line process for cutting die strip 400. Specifically, saw substation 320 cuts die strip 400 into single components each containing a die portion.

The final step in end-of-line assembly portion 300B is performed at the sort substation 322. Sort substation 322 performs an in-line sorting process applied to

each component cut from die strip 400. In general, sort substation 322 is used for separating e.g., categorizing, individual die components into accepted and rejected piles. The specifics of saw substation 320 and sort substation 322 are discussed in more detail herein. At the completion of end-of-line portion 300B, die components  
5 are provided to the tester substation 330 (Fig. 2).

With further reference to step 806 of Figure 8 and Figure 3B, the present embodiment both reduces and modifies most processes and times established by the conventional art, thereby allowing an efficient in-line assembly to be performed. Of  
10 particular significance, PMC substation 316 has been integrated into in-line back-end IC manufacturing line 200. Not only has PMC substation 316 been integrated into the manufacturing methodology of the present embodiment, it is used to accomplish both PMC 122 and dry bake 132 of the conventional art. Additionally, PMC substation 316 includes an annealing portion (e.g. for approx. 20 minutes) to  
15 reduce strip warpage and allow mechanical stress relief. Therefore, in the present embodiment, upon completion of a 175 degree Celsius, 5 hour PMC substation 316, die strip 400 does not require a dry bake 132. Although dry bake 132 has been removed, the resulting components are nevertheless packaged at moisture sensitivity level 3 (MSL 3). Specifically, the ability to remove dry bake 132 is due to  
20 the extremely short cycle time of line 200 following PMC substation 316. In fact, the removal of dry bake 132 advantageously reduces line 200s timeline by at least 24 hours.

Referring still to step 806 of Figure 8 and Figure 3B, the present embodiment establishes new methods for saw substation 320. Generally speaking, conventional saw machines were designed for 8" wafer sawing. However, the present embodiment employs n-by-m matrix array strips. Therefore, the substrate cutting length on the saw is modified (in one embodiment, to 205 mm). In another embodiment, the package sawing machine may be enhanced to allow tape-less singulation (sawing) of molded strips with a length of more than 230 mm. The present modifications achieve a higher unit density, thereby increasing the throughput of the line.

It is appreciated that V/C systems 302 are employed by the end-of-line portion 300B at the mold 314, SBA 318, and sort 322 substations. The interaction of these systems is described further to follow.

With reference now to step 808 of Figure 8 and Figure 2, the present embodiment automatically provides die-strip components 400 from end-of-line assembly portion 300B to a test assembly portion 330 using an in-line fashion.

With reference now to step 810 of Figure 8 and Figure 2, die-strip components 400 are electronically tested using test assembly portion 330. In general, test assembly portion 330 is a quality assurance measure wherein specific components are tested to ensure proper operation. Specifically, test assembly portion 330 can be used to

identify a good or bad die. It may further be utilized to subdivide good die based on performance characteristics such as speed, thermodynamic values, etc. As previously stated, this is accomplished in an automated in-line fashion.

5 With reference now to step 812 of Figure 8 and Figures 2, the present embodiment automatically provides die-strip components 400 from test assembly portion 330 to a finish assembly portion 300C. As illustrated in the previous portions (e.g. 300A and 300B) the need for human interaction within the manufacturing process has been eliminated.

10 With reference now to step 814 of Figure 8 and Figure 3C, the present embodiment processes die-strip components 400 through the finish assembly portion 300C, which comprises a plurality of sub-stations operating on an in-line basis. In one embodiment, the plurality of sub-stations in finish portion 300C  
15 include mark substation 324, final visual inspection (FVI) substation 326, and tape and reel (T/R) substation 328.

In general, in-line finish portion 300C performs the final processes to the components of die strip 400. The first process of in-line finish assembly portion  
20 300C (e.g. performed by mark substation 324) marks the components cut from die strip 400. In the present embodiment the mark is an identifying characteristic enabling the components cut from die strip 400 to be grouped into lots. The mark is

aided by a visual inspection system (e.g. V/C 302) and may further contain a company logo, or any other information the manufacturer may desire.

5 The second step in in-line finish portion 300C is performed by the FVI substation 326. In general, FVI substation 326 performs an in-line process for performing the final visual inspection on die strip 400 components. That is, components of die strip 400 are visually inspected for many technical aspects. A few inspection requirements include assurance that components are complete, that all parts are properly protected, that the sawing process was completed correctly, etc. In 10 the present embodiment, FVI substation 326 is performed using the aid of an in-line automated visual camera (V/C) 302.

15 The final step in in-line finish portion 300C is performed by T/R substation 328. T/R substation 328 performs an in-line process for packaging the components cut from die strip 400. T/R substation 328 is covered in more detail in the universal packaging section herein and uses a visual inspection system V/C 302.

20 In the finish assembly portion 300C, the 24-hour dry bake process of the conventional art has been removed completely. In its place, final visual inspection (FVI) substation 326 occurs. FVI substation 326 utilizes V/C 302 and the integrated software processes of line 200 to inspect the finished components prior to packaging. In one embodiment, packaging is referred to as tape and reel (T/R) substation 328

which places the individual IC chip components into compartments which are taped together and then reeled. The above-mentioned, V/C 302 and integrated software processes will be covered in more detail herein.

5 It is appreciated that embodiments of the present invention utilize a number of automated carriers or conveyors to move die-strips and die-strip components from one substation to another. These conveyors, and the substations themselves, are controlled by a central software application of a computer control system.

10 With reference still to Figure 2, the present embodiment has reduced the overall processing time of a die strip 400 by using a completely in-line technique without human interaction. Specifically, in the conventional art, a production cycle spanned a period of four to six weeks. In the present embodiment, a production cycle takes approximately one day from D/A substation 304 to T/R substation 328.

15 Further, the processing cycle results in an average of 3,600 units per hour for a 48-pin package. The significant increase in productivity is due to a new die-strip 400 not having to wait for a previous die-strip 400 to finish an entire processing cycle. In fact, a new die-strip 400 may enter line 200 in pipeline fashion, e.g., as soon as the previous die-strip 400 has cleared the initial processing step. Therefore, line 200  
20 maintains an efficient, made-to-order process with die-strips being pipelined through the in-line assembly process. The present embodiment further results in

lower labor costs and reduced personnel requirements due to the automation of the assembly line method.

### INTEGRATED SOFTWARE PROCESS

5           With reference now to Figure 12, portions of the present embodiment are comprised of or controlled by computer-readable and computer-executable instructions which reside, for example, in computer-usable media of a computer control system. Figure 12 illustrates an exemplary computer system 1212 that may be used in accordance with one embodiment of the present invention. It is appreciated that system 1212 of Figure 12 is exemplary only and that the present embodiment can operate on or within, or be controlled by, a number of different computer systems including general purpose networked computer systems, embedded computer systems, routers, switches, server devices, client devices, various intermediate devices/nodes, stand alone computer systems, and the like. Additionally, computer system 1212 of Figure 12 is well adapted having computer readable media such as, for example, a floppy disk, a compact disc, and the like coupled thereto.

          System 1212 of Figure 12 includes an address/data bus 1210 for communicating information, and a central processor unit 1201 coupled to bus 1210 for processing information and instructions. System 1212 also includes data storage features such as a computer usable volatile memory 1202, e.g. random access

memory (RAM), coupled to bus 1210 for storing information and instructions for central processor unit 1201, computer usable non-volatile memory 1203, e.g. read only memory (ROM), coupled to bus 1210 for storing static information and instructions for the central processor unit 1201, and a data storage device 1204 (e.g., a magnetic or optical disk and disk drive) coupled to bus 1210 for storing information and instructions. System 1212 of the present embodiment also includes an optional alphanumeric input device 1206 including alphanumeric and function keys coupled to bus 1210 for communicating information and command selections to central processor unit 1201. System 1212 also optionally includes an optional cursor control device 1207 coupled to bus 1210 for communicating user input information and command selections to central processor unit 1201. System 1212 of the present embodiment also includes an optional display device 1205 coupled to bus 1210 for displaying information.

With reference now to process 900 of Figure 9, the present embodiment implements a software process 900 in conjunction with assembly line 200. In one embodiment, the software process 900 takes place on computer control system 1212.

With reference now to step 902 of Figure 9 and Figure 6, a communications protocol is utilized between system 1212 and the in-line substations to control their activity. Specifically, a standard semi equipment communications standard/generic equipment model (SECS/GEM) protocol may be used. Generally speaking, SECS is a



layer 6 protocol that describes the content of the messages while GEM is a higher layer application protocol that defines the messages themselves.

With reference still to step 902 of Figure 9 and Figure 6, the communications protocol is utilized to provide an interface between portions of the integrated in-line back-end IC manufacturing hardware 200. In another embodiment, the communications protocol may be established within each piece of hardware on line 200. As shown in Figure 6, the communications protocol results in a software hierarchy for line 200. In another embodiment, the software hierarchy is established to maintain overall control of line 200. Further, the communications protocol is independent of the hardware platform. Thus, compatible communication between any portion of line 200 is obtained.

With reference now to step 904 of Figure 9 and Figure 6, the present embodiment monitors a portion of line 200 using a manufacturing execution system (MES) 600 coupled with the communications protocol. Furthermore, MES 600 may be comprised of at least one equipment cell controller (CC). In the present embodiment, MES 600 may also be comprised of two CCs. Specifically, a portion of front-of-line hardware 300A is coupled with front-of-line equipment cell controllers (CC) 602, and a portion of end-of-line hardware 300B is coupled with end-of-line equipment CC 604. Both CC 602 and CC 604 are then coupled to communicate with MES 600 for command and control. In one embodiment, MES 600 maintains a

planning database 620 which includes a die-strip map database. In another embodiment, MES 600 controls the processing activities at each substation.

Accordingly, all lot movement and process-monitoring details are regularly updated to MES 600 and ultimately the planning database 620 via both CC 602 and CC 604. In

5 another embodiment, planning database 620 is further utilized to maintain an internal planning and/or order/shipment database. However, in order to maintain comprehensive tracking of lot movement and process-monitoring details, a system to differentiate each die-strip 400 is instituted. The specifics of the system to differentiate each die-strip 400 will be discussed in detail herein.

10 A further example of multiple embodiments of the software hierarchy is illustrated in Figure 13. Specifically, Figure 13 is a representation of the steps taken by the visual system, e.g., V/C 302, to view the die-strip 400. The results of their inspections are collected by CC 602 and CC 604 units and are then transferred to the  
15 central MES 600 system. In one embodiment, the inspection results are further transferred to database 620. In general the three columns (e.g. die-strips i, i+1, and i+2) represent portions of a die-strip 400 die map. Specifically, boxes F1-F8 represent mapping, while E1-E4 represent other parameters collected at other visual stations. All boxes represent process history information including individual die-strip map  
20 database (e.g. 620) and inspection (e.g. quality assurance (QA) 1 1310 and QA2 1320. As stated herein, all data collected by V/C 302 systems is stored in a database that maintains each die-strip 400s' processing history. Although a specific hierarchy of

computer systems is established, the present embodiment is well suited to many types of computer system hierarchy. Additionally, the present embodiment of computer system hierarchy is illustrated for purposes of clarity, not as a means of limitation.

5

## REJECT MANAGEMENT

In one embodiment, reject management is a portion of the in-line assembly line manufacturing process that utilizes the integrated software processes mentioned herein to determine the manufacturing status, quality, and performance of each specific die on a die-strip 400. In general, aspects of reject management detailed herein allow comprehensive tracking and quality assurance of a die-strip 400 and every die thereon ensuring a high level of "out-the-door" product quality. Reject management is dependent on accurate V/C 302 calibration and integration with the software database 620.

10

15

With reference now to step 1002 of Figure 10 and Figure 5, the present embodiment implements an automated and database driven tracking process for die-strip 400 which uses the camera vision systems to automatically identify individual die-strips 400 and their respective locations as they traverse through the in-line assembly line 200. In one embodiment, the tracking process starts at die attach substation 304 and is maintained throughout the entire back-end IC manufacturing process. However, in order to maintain a die-strip level tracking

20

process, a two-dimensional code, known as data matrix 2D symbol 510 may be placed on every die-strip 400. In one embodiment, data matrix 2D symbol 510 is etched onto die-strip 400 by a laser. However any printing or affixing method could be used.

5

Specifically, each data matrix 2D symbol 510 utilizes a specialized 2D matrix code similar to a bar code. Data matrix 2D symbol 510 may store up to 19 characters, in one embodiment, which maintain all specific chip and lot related information. Further, a second data matrix 2D symbol 510 may also be placed on die-strip 400.

10 This second data matrix 2D symbol 510 is analogous to the first data matrix 2D symbol 510 and may be utilized as a back up. Therefore, if any damage occurs to the first data matrix 2D symbol 510, the die-strip tracking process remains possible by utilizing back-up data matrix 2D symbol 510. In a second case, a combination of both first data matrix 2D symbol 510 and back-up data matrix 2D symbol 510 may be used  
15 for tracking recognition purposes.

With reference now to step 1004 of Figure 10 and Figure 6, the present embodiment accesses an electronic die-strip map database 620 that provides parameter storage for each individual IC component within each die-strip 400. In  
20 one embodiment, the electronic die-strip map database 620 is located in memory on MES 600. In general, the electronic die-strip map database 620 maintains a record of each die-strip 400 traversing the individual substations of the manufacturing

process. Specifically, the electronic die-strip map database 620 maintains information relative to the die-strip level as well as information regarding inspection and processing at the individual die level.

5           An example of the electronic die-strip map database 620 is illustrated in Figure 4. Specifically, a single die-strip 400 is shown in a visual representation of the electronic die-strip map database 620. The database 620 records parameters for each chip on the die-strip 400 and these parameters are updated as the die strip traverses through the manufacturing process thereby providing a process history for the die-strip 400. For instance, 164 individual die are illustrated on a matrix substrate, or leadframe, in an array-like structure on die-strip 400. On each die a representative letter is shown as a parameter within a designated die block. In one embodiment, the letter is either a G or a B. Specifically, G is a reference to good, while B is a reference to bad.

10           During the manufacturing process, any changes to the status of a specific die are updated by the electronic die-strip map database 620. A negative update to the strip map would result in a change on die-strip 400 from a die block being designated with a G to a new designation of B. The designations of G and B are simplified  
15           examples of an actual electronic die-strip map database 620. Further, any representation resulting in differentiation between satisfactory and unsatisfactory die located on die-strip 400 may be utilized by the present embodiment. A further

example of differentiation is the parameter of test speed. For instance, the die-strip map database 620 could also categorize die based on performance data, such as speed, etc.

5 With reference now to step 1006 of Figure 10 and Figure 5, the present embodiment utilizes the tracking process to update the electronic die-strip map database 620 at each substation that collects parameter information throughout the manufacturing process. Specifically, die-strip 400 is analyzed at each key process by V/C 302. In one embodiment, V/C 302 is used to inspect a portion of the die on die-  
10 strip 400 for physical attributes. Parameters are then updated for each die in the database 620. In another embodiment, V/C 302 is used as a data matrix 2D symbol 510 reader for location determination by identifying the die-strip 400. For example, the analysis of die-strip 400 in a front-of-line portion 300A is conducted by V/C 302. Further, the data matrix 2D symbol 510 on the same die-strip 400 is read by V/C 302.  
15 The results of both V/C 302 processes are reported to CC 602. CC 602 then passes the information to the electronic die-strip map database 620 located on MES 600. This information is then processed by the electronic die-strip map database 620. In so doing, the updated electronic die-strip map database 620 will continue to maintain a positive track of a portion of the die on die-strip 400.

20 Although in the present embodiment V/C 302 are used as a data matrix 2D symbol 510 reader, a distinct 2D code reader may be installed at the strip entry point

of a substation of processing equipment that will update and/or use the strip map database 620. The utilization of V/C 302 as the 2D code reader and die-strip 400 inspector are merely for purposes of brevity. It is further appreciated that each automated V/C 302 may be independent from, or in electronic communication with, any or all other automated V/C 302.

With reference still to step 1006 of Figure 10 and Figure 5, in the present embodiment V/C 302, the tracking process, and the electronic die-strip map database 620 are the tools that have improved the tracking, inspecting, and dehumanization of the back-end IC manufacturing process. Specifically, the reliability of V/C 302 in the electronic die-strip mapping process is important. V/C 302 is utilized for data matrix 2D symbol 510 reading and verification. For example, V/C 302 automatically recognizes the die-strip 400 by reading the data matrix 2D symbol 510 at different points throughout the in-line manufacturing process. V/C 302 is further used for visually inspecting die-strip 400 and the die thereon throughout the in-line manufacturing process. Specifically, the present embodiment uses V/C 302 inspection after some of the major process steps, for example, die attach substation 304, W/B substation 310, mold substation 314, SBA substation 318, and saw substation 320. In another embodiment, V/C 302 inspection is used after all of the major process steps. Accordingly, utilizing V/C 302 for both inspection of die-strip 400 and a portion of the die on die-strip 400, as previously stated, allows the present embodiment to replace human inspectors with automated inspection techniques.

As a result, completion times of the in-line assembly line process are markedly improved.

There are many reasons why automated inspection is preferred to human inspection. A major reason is the quantity of inspection capabilities. In the conventional process, initial human inspection is conducted on a portion of the batch. Each initial human inspection is then followed by a human QA inspection of a smaller portion of the same batch. This redundancy is established to ensure a quality product. However, in one embodiment of the present invention, all of the die on each die-strip 400 may be inspected. Thus, a complete inspection capability is obtained. Such a capability allows for higher product reliability.

A second reason for automation is the specific inspection method. In human inspection, each inspector brings a personality to the inspection process. Further, the inspection station has rotating personnel. Therefore, the inspection techniques differ per inspector. In an automated inspection process, no personality is involved and V/C 302 is in constant operation. Further, each V/C 302 is calibrated and all V/C 302 maintain a similar standard for inspection.

A third reason for automation over human inspection is the contact factor. For example, when a human inspects a batch, purposeful or incidental contact of either die-strip 400 or a die thereon may occur during the inspection process. With



an automated inspection system, there is no need for V/C 302 to make any sort of contact with die-strip 400 or any die thereon. Thus, all incidental damage caused by the inspector or the inspection is removed.

5           Therefore, it is appreciated that each of the preceding aspects of automated inspection result in an increase in productivity. Additionally, an increase in quality and quantity of product is realized due to better inspection practices. A further benefit is the reduction of collateral damage due to the removal of any incidental human contact.

10           With reference now to step 1008 of Figure 10 and Figure 6, the present embodiment categorizes the die on die-strip 400 based on information maintained by the electronic die-strip map database 620. Specifically, the electronic die-strip map is continuously updated at each inspection step, on the die-strip map server by V/C  
15   302. Thus, the electronic die-strip map database 620 maintains the complete processing history of die-strip 400. This map database 620 can then be used to physically separate die into bins of similar categories.

20           Therefore, with reference to Figures 6 and 7, when die-strip 400 reaches saw substation 320 and sort substation 322, the electronic die-strip map is downloaded and the information is used to automatically sort and reject the designated "bad" units. Sorting may be performed based on any managed parameters. Specifically,

the reject management protocols utilize the electronic die-strip map database 620 categories and either accept or reject each die. In another embodiment, subsequent rejection processes take place following the testing, marking, and final visual inspection steps of the integrated in-line IC assembly method. At each rejection evaluation, accepted units continue the process while any rejected units are automatically placed in reject bins 610. Further, it is possible for the electronic die-strip map database 620 to isolate specific rejected units on die-strip 400 early in the in-line manufacturing process such that no further back-end IC manufacturing processes are performed on the rejected units. In fact, rejected components, which are identified early in the manufacturing process, remain in their rejected state on die-strip 400 until reaching sort substation 322. At that point, all rejected units are deposited in reject bins 610. Thus, valuable manufacturing materials are saved for use on accepted units. In one embodiment, when a unit has passed all required evaluations and completed the tape and reel substation 328 of the in-line assembly process, the reel is then placed in a good bin 710.

With reference still to step 1008 of Figure 10, the present embodiment further utilizes the electronic die-strip map database 620 to establish a processing history for tracking material usage and equipment details, and preventing the mixing of chips. Another added benefit of having a processing history, are the improved defect analysis features. Specifically, the processing history may be used to isolate exact areas within die-strip 400 or a substation of the integrated in-line back-end IC

manufacturing process correlated with recurring defects. Thus, it is then possible to establish preventive maintenance techniques, such as, statistical process control (SPC) which predict and identify/repair these defective zones thereby increasing productivity.

5

### UNIVERSAL PACKAGING

In one embodiment, universal packaging is a portion of the in-line assembly line manufacturing process which utilizes updated subassemblies mentioned herein in accordance with the integrated software processes disclosed. In general, aspects of universal packaging detailed herein allow package changeovers with minimal changeover times, thus allowing some amount of flexibility within package families. For example, an exemplary changeover in the entire line from a 7mm x 7mm package to any other package size may take less than thirty minutes.

With reference now to step 1102 of Figure 11 and Figure 6, an electronic die-strip map database 620 is accessed. Specifically, mold 314 of portion 300B is established as the introductory point, in process 650, for the universal packaging process. As stated above, mold 314 is the step in the back-end IC manufacturing process wherein the die above die-strip 400 is covered in a protective coating. In one embodiment, the protective coating is a type of plastic. Moreover, the protective coating is placed in a specific location on die-strip 400. That is independent of any actual die shape. In fact, mold 314 is a standard process applied to each die-strip 400.

As such, there is no need for modification of mold 314 process per specific die size run. Thus, any mechanical or manufacturing modifications required by mold 314 are reduced. Specifically, as long as the size of die-strip 400 remains constant, the size of the die on die-strip 400 is immaterial. In addition, die-strip 400 may utilize  
5 either plastic or copper as the strip portion for die attachment without any detrimental effects.

With further reference to process 1102 of Figure 11 and Figure 6, the integrated solder ball attach (SBA) substation 318 process is also universal. That is,  
10 in the present embodiment, SBA substation 318 process is independent of solder ball type. The specific choice is related to outside manufacturing costs and desired integrated chip requirements. In general, the integrated in-line back-end IC manufacturing process SBA substation 318 is similar in process to mold 314. That is, SBA substation 318 is also used at die-strip 400 level. Therefore, no matter what size  
15 die is above die-strip 400, SBA substation 318 uses the same universal attachment method. Because of the universality of SBA substation 318, there is no need to retool SBA substation 318 in order to process a different size die as long as die-strip 400 remains constant.

20 With reference now to step 1104 of Figure 11 and Figure 6, die-strip 400 is automatically cut based on information maintained by the electronic die-strip map database 620. Specifically, due to the universality of both mold 314 and SBA 318

substations, die-strip 400 arrives at saw substation 320 in a uniform format. Saw substation 320 then requires specific instructions about the die specifications in order to cut die-strip 400 without damaging any individual die thereon. Specifically, saw substation 320 is informed of the specific cutting specifications by the electronic strip-map database 620. As stated above, the electronic strip-map database 620 maintains the complete strip processing history of die-strip 400. Hence, when saw substation 320 receives the cutting specifications, it is able to cut die-strip 400 into the specified components without any human interaction while maintaining the integrated assembly line back-end IC manufacturing format. The resulting cut die components are then individually packaged at T/R substation 328 using, in one embodiment, the industry standard quad flat packaging with no lead (QFN).

Thus, the present invention provides, in various embodiments, a method and system for universal packaging in conjunction with a back-end IC manufacturing process. Embodiments of the present invention also include a method and system for universal packaging in conjunction with a back-end IC manufacturing process which can proficiently perform IC packaging in an in-line fashion. The present invention further provides a method and system for universal packaging in conjunction with a back-end IC manufacturing process which can curtail human visual inspection and QA process by using automated vision systems to maintain a higher quality of visual inspection. The present invention also provides a method and system for universal packaging in

conjunction with a back-end IC manufacturing process which requires fewer personnel to maintain a packaging line. The present invention further provides a method and system for universal packaging in conjunction with a back-end IC manufacturing process which is compatible with existing back-end IC manufacturing processes.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents.